

ASPL - Aluminium Screw Platform Light

Order:

Inquiry:

Date:

Company:

Telephone:

Quantity/pieces:

Name:

E-Mail:

Commission:

Address:

Chassis:

Cab length:

VEHICLE BODY:

Gross Vehicle Weight ≤ 3,5 t

Gross Vehicle Weight > 3,5 t ≤ 7,5 t

Clear dimension

Overall dimensions

FRONT WALL: (from 300 – 1,600 mm)

Height: mm

White position light in front wall pillar

Yes No

PLATFORM PRE-ASSEMBLED:

Bridge mounting and plywood panels NOT pre-assembled.

Yes No

SUBFRAME:

Distance: mm

UNDERFRAME SUBFRAME:

Length: mm

Width: mm



110 mm

130 mm

160 mm

without subframe
= Third-party subframe

SIDEBOARDS (from 300 – 500 mm)

Height: mm

SIDEBOARDS (Sectioning recommended from approx. 4,000 mm)

Continuous

Sectioned

SIDEBOARD VERSION

Smooth

Tarp tensioning profile

Flat eyelet profile

With airline profile

FLOOR

Phenolik plywood board 18 mm

Aluminium 18 mm

OPTIONAL

Additional Airline fitting

Recessed folding tread plate

Sliding folding tread plate

Bridge mounting

FLOOR FRAME

Yellow side marker light in the lateral floor frame
Mandatory for overall vehicle length > 6000 mm

Yes No

Red position light in the rear floor frame

Yes No

ASPL - Aluminium Screw Platform Light

Load securing

< gross vehicle weight 3,5 t / double fitting with ring
> 3,5 gross vehicle weight and ≤ 7,5 t gross vehicle weight / quadruple fitting with hinge



S-Line® Double airline fitting 571

Steel, Ø inner ring 42 mm,
breaking load 2700 daN, weight 0,16 kg.

142138571



S-Line® Quadruple airline fitting 702

Steel, foldable, Ø inner ring 24 × 62 mm, breaking load 5000 daN,
weight 0,397 kg.

142138702



S-Line® Sliding block for airline track

Galvanised steel, 2 M8 holes, 2 M6 holes, weight 0.01 kg.
Without screw material.

142138544



To the ASPL
product video

© 2025 Suer Nutzfahrzeugtechnik GmbH & Co. KG - Subject to technical and errors excepted.

